

NOTES:

- 1. INSTALL PHOTO ELECTRIC CELL (P.E.C.) ON POLE CAP. USE <u>TWISTLOCK TYPE</u>, SEE DETAIL. SEE CITY OF KIRKLAND INSPECTOR FOR PART NUMBERS OR EQUIVALENT. FACTORY INSTALLED P.E.C. IS NOT ACCEPTABLE.
- 2. WIRES FROM J-BOX, OUTLET, AND BALLAST WILL BE CONNECTED AT THIS AREA; NOT BY THE SLIP JOINT.
- 3. THE ONLY CONNECTION MADE AT HAND HOLE IS THE POLE GROUNDING CONNECTION.
- 4. WITH SLOPED SIDE WALKS, THE POLE BASE MUST PROTRUDE ABOVE FINISHED GRADE SO THAT BASE COVER WILL SIT LEVEL.
- 5. PS ORIENTATION UNDERNEATH LIGHT UNLESS OTHERWISE DESIGNATED.
- 6. LIGHTS SHALL BE GENERALLY SPACED AT 60' ON CENTER.
- 7. ALL PEDESTRIAN LIGHTS SHALL HAVE 1 SIGN BRACKET.



PLAN NO. CK-R.47



CENTRAL BUSINESS
DISTRICT STREET
LIGHT STANDARD